Typical Application

- · Semiconductor applications.
- Detection of organic contamination on PCB and electronic components.
- · Evaluation of cleanliness / treatment / coating processing.
- · Hydrophobicity and hydrophilicity of solid surfaces.
- Biological application such as the detection and characterization of proteins.
- · Adsorption / wettability of powder and pharmacy.
- Analysis of plasma treatments to increase the wettability on polymers surfaces.

Technical Data

· Sample size Virtually unlimited

Max Measuring speed 70 FPS
Light Source LED
Contact Angle range 3~180°
Accuracy ± 0.1° deg
Connecting type USB

Operating system
 Dimension (mm)
 Windows XP, Window 7, Window 8
 90(H) except syringe height x 90(W) x 50(D)

· Weight 450g

Option

· Software control tilting stage





www.s-eo.com

SEO (Surface Electro Optics)

#946, Kosekdong, Suwon City, Kyunggido, 441-813, Korea

Phone: +82.31.298.9561 Fax: +82.31.298.9565 E-mail: seo@s-eo.com





Contact Angle Analyzer



Phoenix-i

The phoenix series is designed to offer the flexibility required QA, R&D and engineering process development.

Phoenix-i is a quite simple and virtually measure any sample size without sample cutting prepare.

Light-weight means simply control device and simply handling. Phoenix-i adopted USB type camera. Easily connect to note book and desk top computer device with Surfaceware8 software.

Features

- · Data checking instantly without open analysis window by preciew result function
- · High-resolution and powerful image capture system
- · Available to connect to Notebook or Desktop PC via USB port
- · Improved precision and reproducibility by the elimination of operator error
- · Inside of device condition checking window
- · Light-weight
- · LED light source

Capabilities

- · Static contact angles
- · Sequence image capture by appointed interval time basis
- · Surface energy
- · Real time contact angle display (preview function)
- · Sessile drop / surface tension by pendent drop method.
- · Precise calculate drop volume.
- · Data comparison function.

